


SMD TYPE CERAMIC OSCILLATORS



NAON Series 2.0 x 1.6

  	Application :
	- Portable PC / Digital camera - Wireless Lan / DOA Terminal - Portable multimedia player - PCMCIA card / SD card - CCD / HDD
	Features :
	- Low power consumption - RoHS compliant / Pb free - Excellent solderability - Seam welding - Tri-State



Electrical Specification :

Model		NAON-21		
1. Frequency				
Frequency Range	MHz	4.0 ~ 125.0		
Frequency Stability	PPM	A: ±100 B: ±50 C: ±30 D: ±25		
Operating Temp Range	°C	0 ~ +70, -40 ~ +85 or specify		
Storage Temp Range	°C	-55 ~ +125		
Output Level		CMOS		
Output Symmetry	%	40% ~ 60% (at 50%VDC)		
Power Supply Voltage	VDC	3.3V±10%	2.5V±5%	1.8V±5%
2. Current Consumption				
4.00 MHz ~ 9.99 MHz	mA Max.	7	6	6
10.00 MHz ~ 19.99 MHz		7	8	8
20.00 MHz ~ 31.99 MHz		12	8	8
32.00 MHz ~ 50.00 MHz		20	20	20
50.01 MHz ~ 125.0 MHz		30	30	30
3. Rise and Fall Time				

* Above specification subject to change without prior notice, please consult our sales representative for more information*

SHENZHEN - Shenzhen Huilicheng Electronic Technology Co.,Ltd. HONGKONG - HUILICHENG ELECTRONICS(HK)CO.,LIMITED

Address: 6910b,Seg Plaza,No.1002 North Huaqiang Road,Fuqiang Community,Huaqiang North Street,Shenzhen,Guangdong,China

Tel: +86-0755-83576022

E-mail: hlc-zzw@hlcdzjkj.com

Fax: 0755-83778079

Web: <http://www.hlcdzjkj.com>


SMD TYPE CERAMIC OSCILLATORS



4.00 MHz ~ 9.99 MHz	ns Max.	6	7	7
10.00 MHz ~ 19.99 MHz		6	7	7
20.00 MHz ~ 31.99 MHz		5	6	6
32.00 MHz ~ 50.00 MHz		5	9	9
50.01 MHz ~ 125.0 MHz		5	9	9
4. Output Load	pF	15		
5. Aging	PPM/Year	±3		



Dimensions (mm) :



#1: ENABLE / DISABLE FUNCTION

INH (PIN 1)	→	OUTPUT (PIN 3)	# NO.: define	
High (OPEN)	→	Operating	#4: VDD	#3: OUTPUT
LOW	→	High impedance	#1: E/D	#2: GND

* Above specification subject to change without prior notice, please consult our sales representative for more information*

SHENZHEN - Shenzhen Huilicheng Electronic Technology Co.,Ltd. HONGKONG - HUILICHENG ELECTRONICS(HK)CO.,LIMITED

Address: 6910b,Seg Plaza,No.1002 North Huaqiang Road,Fuqiang Community,Huaqiang North Street,Shenzhen,Guangdong,China


Tel: +86-0755-83576022

E-mail: hlc-zzw@hlc-dzjk.com


Fax: 0755-83778079

Web: <http://www.hlc-dzjk.com>


Tape Specification(mm) :



Reel Packing(mm) :



Reflow Temperature Profile :



* Above specification subject to change without prior notice, please consult our sales representative for more information*

SHENZHEN - Shenzhen Huilicheng Electronic Technology Co.,Ltd. HONGKONG - HUILICHENG ELECTRONICS(HK)CO.,LIMITED

Address: 6910b,Seg Plaza,No.1002 North Huaqiang Road,Fuqiang Community,Huaqiang North Street,Shenzhen,Guangdong,China

Tel: +86-0755-83576022

E-mail: hlc-zzw@hlcdzjk.com

Fax: 0755-83778079

Web: <http://www.hlcdzjk.com>