




NAPK Series 3.2 x 2.5

  	Application :
	- XDSL / SONET / SDH - Wideband WLAN AP 1G /10G Ethernet - Fiber Channel
	Features :
	- Low phase jitter (12KHz to 20MHz) under 1 ps (RMS) - Low profile package design (1.1mm height max.) - Tri-state function available - Differential output



Electrical Specification :

Model		NAPK-32
1. Frequency		
Frequency Range	MHz	25.0 ~ 200.0
Frequency Stability	PPM	A: ±100 B: ±50 C: ±30 D: ±25
2. Temperature Range		
Operating Temp Range	°C	-10 ~ +70, -40 ~ +85 or specify
Storage Temp Range	°C	-55 ~ +125
Output Voltage High (V _{OH})	V (Min.)	1.025 VDD
Output Voltage Low (V _{OL})	V (Max.)	1.625 VDD
Output Load	Ω	50
Output Symmetry	%	45% ~ 55%
3. Input Voltage		
Enable High Input Voltage	V (Min.)	0.7 VDD
Enable Low Input Voltage	V (Max.)	0.3 VDD
Current	mA (Max.)	80
Rise / Fall Time (20% / 80%)	nS (Max.)	1.0
Aging	PPM / Year	±3
Start Up Time	mS (Max.)	10

* Above specification subject to change without prior notice, please consult our sales representative for more information*

SHENZHEN - Shenzhen Huilicheng Electronic Technology Co.,Ltd. HONGKONG - HUILICHENG ELECTRONICS(HK)CO.,LIMITED

Address: 6910b,Seg Plaza,No.1002 North Huaqiang Road,Fuqiang Community,Huaqiang North Street,Shenzhen,Guangdong,China

Tel: +86-0755-83576022


E-mail: hlc-zzw@hlcdzjkj.com

Fax: 0755-83778079

Web: <http://www.hlcdzjkj.com>



Dimensions (mm) :



# NO.: Pin define		
#6: Vcc	#5: QN	#4: Q
#1: E/D	#2: NC	#3: GND

Technical drawing of a fan showing front and side views with dimensions.

Front View (Left):

- Overall diameter: $\phi 180.0$
- Central hub diameter: $\phi 2.0$
- Blade count: 5 blades
- Blade angle: 120°
- Label position: Centered at the top of the hub.

Side View (Right):

- Overall height: 10.9
- Hub height: 1.6
- Blade height: $\phi 13.0$
- Base diameter: $\phi 62.0$

Temperature (°C)

255±5°C

217°C

180°C

150±5°C

0°C

60~120sec

45~90sec

10sec Max.

Pre-Heat

Reflow

Cool

Time (seconds)

Total Time :200sec (Max.)

(s)

Web: <http://www.hlcdzkj.com>